

COLOR SOLUTIONS BASECOAT EXCLUSIVES PURPLE HAZE



GENERAL TECHNICAL DESCRIPTION

Limited edition triple-stage color.

Part of COLOR SOLUTIONS BASECOAT EXCLUSIVES Series.

SURFACE

Old sanded paintwork
Wet-on-wet primed surfaces
OEM sanded surfaces
On surfaces primed with HB BODY BLACK ACRYLIC PRIMER

PRETREATMENT/CLEANING OF SUBSTRATE



Clean substrate using a soft cloth and 770 ANTISIL NORMAL / 771 ANTISIL FAST DEGREASER.

Make sure the surface is first wiped dry and then air dried.

PRODUCT APPLICATION

1ST STAGE



COLOR SOLUTIONS BASECOAT 930-BL



5% H753 HARDENER FOR TOPCOATS NORMAL



50% 760 BASECOAT THINNER NORMAL



Apply 2 coats
1.2 - 1.3mm
1.7 - 2.2 (25 - 32 psi)



10 - 20 min / 23°C (73°F)
Flash off time



20 - 40 min / 23°C (73°F)

2ND STAGE



COLOR SOLUTIONS BASECOAT PURPLE HAZE



5% H753 HARDENER FOR TOPCOATS NORMAL



50% 760 BASECOAT THINNER NORMAL



Apply 2 coats and an effect coat
1.2 - 1.3mm
1.7 - 2.2 (25 - 32 psi)



10 - 20 min / 23°C (73°F)
Flash off time



20 - 40 min / 23°C (73°F)

TOP COAT

C894 / H734 / 5% 741 / NO BAKE (see TDS for application details)

SPECIFIC GRAVITY

0.9 - 0.98 g/cm³ *

SOLID CONTENT

(NO THINNER)

1st Layer - 22 ± 2%

2nd Layer - 10 ± 2%

VOC (2004/42/EC)

This is a special refinish product based on its ingredients and its properties. The maximum VOC content in this category is 840 g/L. The VOC content in ready for use form of this product is 840 g/L.
2004/42/IB(e)(840)840

THEORETICAL COVERAGE

10 - 12 m² / l at 20 micron (0.8 mil) dry film thickness

CLEANING OF EQUIPMENT

Clean after final use with 740 ACRYL NORMAL Thinner / Reducer

REMARKS

- After preparing the area to be painted ensure that it is free from dirt, wax, oil etc.
- Application temperature from 15 - 35°C (59 - 95°F).

STORAGE SHELF LIFE

Guaranteed shelf life of 24 months in unused original containers stored in a cool place (5 - 25°C) (41 - 77°F).

* Specific gravity values lie within a range and depend on the color shade.



Always wear protective equipment



Follow the application instructions mentioned in this TDS

For professional use only. The information displayed on this sheet has been carefully selected through a series of laboratory investigations. It is based on our best knowledge at the time of issue. The data is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check for newer updates or further information if needed for his intended purpose. The intellectual property of this product, trademarks and copyrights is protected. All rights reserved. The relevant Material Safety Data Sheet and warnings displayed on the label must be read carefully. We may modify and / or discontinue operation of all or portions of this information at any time in our sole discretion, without any notice and assume no responsibility to update the information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.